

{Stationary - Skid-Mount}

HDC Series Gasoline - Belt Drive

The HDC Series' is the most affordable and efficient skid on the market today. The best buy for a quick return on investment.

1 NEW model with Kubota diesel engine



HDC-3005-OV6G shown with adjustable temperature control (HX-0145) option



High quality fuel filter/water separator ensures clean fuel supply

Stainless-steel coil wrap



12-volt burner (battery not included)



Polyethylene engine and burner fuel tanks



Large polyethylene float tank



Additional Features:

- ✓ Performance-proven industrial gasoline engine with electric start or liquid-cooled Kubota diesel engine (battery included on Kubota engine)
- ✓ Belt drive triplex General or AR pump with ceramic plungers
- ✓ Forged brass manifold with removable valve caps
- ✓ Factory preset unloader (3000- to 4000-PSI models)
- ✓ High pressure detergent injection
- ✓ 1/2-inch schedule 80-coil with stainless-steel wrap heat exchanger
- ✓ Pressure relief valve protects against excessive system pressure
- ✓ Temperature rise 150°F/66°C above ambient, maximum 200°F
- ✓ No. 1 or No. 2 diesel or kerosene fired burner
- ✓ 10.0-gallon fuel tank capacity
- ✓ 10.0-gallon burner tank capacity
- ✓ Heavy-duty powder coated steel square tube frame
- ✓ 50-foot x 3/8-inch steel wire-braided pressure hose with quick connects
- ✓ Professional-grade insulated trigger gun with safety lock-off
- ✓ Adjustable pressure insulated dual lance



Specifications:

Model #	HDC-3005-0K6G	HDC-3005-0V6G	HDC-3505-0B7G*	HDC-3505-0H6G	HDC-3505-0K6G	HDC-3505-0V6G
Pressure (psi)	3000	3000	3500	3500	3500	3500
Flow (gpm)	4.8	4.8	4.7	4.7	4.7	4.7
Engine	Kohler	Vanguard OHV	Kubota	Honda OHV	Kohler	Vanguard OHV
Horsepower	18.0	16.0	15.5	20.0	20.0	23.0
Fuel Cons. (gph)	2.76	2.76	2.76	2.76	2.76	2.76
BTU per hour	386,400	386,400	386,400	386,400	386,400	386,400
Dim. (LxWxH)	50in.x34in.x45in.	50in.x34in.x45in.	56.5in.x34in.x45in.	50in.x34in.x45in.	50in.x34in.x45in.	50in.x34in.x45in.
Shipping weight	844 lbs.	844 lbs.	940 lbs.	844 lbs.	844 lbs.	844 lbs.
Net weight	725 lbs.	725 lbs.	836 lbs.	725 lbs.	725 lbs.	725 lbs.


Model #	HDC-4004-0H6A ^	HDC-4004-0K6A ^	HDC-4004-0V6A ^
Pressure (psi)	4000	4000	4000
Flow (gpm)	4.0	4.0	4.0
Engine	Honda OHV	Kohler	Vanguard OHV
Horsepower	20.0	20.0	23.0
Fuel Cons. (gph)	2.45	2.45	2.45
BTU per hour	343,000	343,000	343,000
Dim. (LxWxH)	50in.x34in.x45in.	50in.x34in.x45in.	50in.x34in.x45in.
Shipping weight	844 lbs.	844 lbs.	844 lbs.
Net weight	725 lbs.	725 lbs.	725 lbs.

*Diesel unit.

^Models equipped with AR pump, all other models equipped with General pumps.



HDC-3505-0H6G



Options:

- 50-0170 **Stack adapter** - Allows 8-inch flue pipe to be installed to boiler exhaust port
- 850-0324 **Gasket (for 50-0170)** - Seals between 50-0170 stack adapter and boiler housing
- AW-5740-0000 **Wheel kit** - Allows unit to become portable
- HX-0130 **Three-way ball valve** - Allows pressure washer to be operated from garden hose/float tank or trailer supply tank by adjusting ball valve lever
- HX-0145 **Adjustable temperature control** - Operator is able to adjust outlet water temperature between 96°-198°F
- HX-0147 **Four (4) point lifting capability** - Allows unit to be lifted by crane
- HX-0156 **Hour meter** - Displays number of hours unit has been in operation

Model #	50-0170	850-0324	AW-5740-0000	HX-0130	HX-0145	HX-0147	HX-0156
HDC-3005	●	●	●	●	●	●	●
HDC-3505	●	●	●	●	●	●	●
HDC-4004	●	●	●	●	●	●	●