



INDUSTRIAL CLEANING DETERGENT SPECIALISTS

PRODUCT INFORMATION SHEET



TACKLETM

“Free Rinsing” MULTI-USE DETERGENT


MODERATELY ALKALINE

Available
through




TACKLE is a moderately alkaline clear liquid detergent with a wide variety of applications. It is a great brushless commercial truck wash and building & siding cleaner! **TACKLE** cuts through heavy caked-on grease found on motors and heavy equipment. It also cleans and brightens dull, oxidized aluminum surfaces. Cleans everything in transportation, industrial facilities and warehousing operations, is biodegradable and USDA approved. Ideal for use with hot or cold water, steam or high pressure washers. (Do not use on polished aluminum surfaces.)

APPLICATIONS



Commercial
Truck Fleets



Food Processing
Plants



Building
Siding Wash



Dull Aluminum
Brightening



Waste
Haulers



Oil
Refineries

★	BRUSHLESS VEHICLE WASHING	DILUTE 30 to 1	Draw and apply product through a high pressure washer. Apply from bottom to top. Let set. Rinse from top to bottom.
★	HEAVY DEGREASING	DILUTE 20 to 1	Best results are obtained when product is drawn and applied under Hot high pressure. For cold low pressure use, pre-soak objects with more concentrated product then pressure rinse or steam clean.
★	HOUSE CLEANING/ BUILDING WASHING	DILUTE 25 to 1	Draw and apply product through a high pressure washer. Let set, Then high pressure rinse.
★	ALUMINUM BRIGHTNING	DILUTE 1 to 1	Apply product by spray, from bottom to top and let set. High pressure rinse from top to bottom. Repeat as needed. CAUTION: Makes bad aluminum look good, and highly polished aluminum look bad.
★	CONCRETE OIL STAIN REMOVER	DILUTE 10 to 1	Best results are obtained when product is drawn and applied under Hot high pressure. For cold low pressure use, pre-soak soils with more concentrated product then pressure rinse.
★	A/C ALUMINUM COIL CLEANING	DILUTE 3 to 1	Pre-spray straight or diluted product through a trigger or pump up sprayer. Let set, then low pressure rinse.
★	COMMERCIAL FLOOR MOPPING	DILUTE 15 to 1	Add product to a warm bucket of water and mop as usual.

DETAILED SPECIFICATIONS

Viscosity	Free flowing liquid	Biodegradability	Complete
Color	Clear	Phosphate Content	None
Odor	Slight	Stability	3 years
pH Concentrate	10.9	Sudsing	Moderate
Specific Gravity	1.045 + - 0.005 gm/ml	Hard Water Stability	Excellent

PACKAGING

TACKLE is available in 1 gallon, 5 gallon and 55 gallon containers and through the **ETS ALL-STAR DELIVERY PROGRAM**.

CAUTION: CORROSIVE.
Avoid Contact with skin and eyes. Do not take internally.
KEEP OUT OF THE REACH OF CHILDREN
(See Material Safety Data Sheet)