

**NEW
10,000 PSI**
**High Pressure Industrial
Specialty Pump**



**Triplex Positive
Displacement Pump**

- Low upswept volume maximizes volumetric efficiency.
- Special UHMV supported V-packings for high pressure stability and extended life.

Typical Applications

Hydrostatic Testing
 Chemical Injection
 Surface Prep/Tube Cleaning
 High Pressure Tooling
 Blow Off Preventer (BOP)
 Railroad Undercarriage and
 Tank Car Cleaning
 Oilfield Washdown
 Marine Barnacle Growth/Paint
 Removal
 Sewer Drain Blasting
 Heavy Equipment Cleaning

Model 1810
10,000 PSI, 3.0 GPM, 1500 RPM

SPECIFICATIONS	U.S. Measure	Metric Measure
Inlet Pressure Range	Flooded to 60 PSI	Flooded to 4 BAR
Crankcase Capacity	42 oz	1.26 L
Maximum Liquid Temperature	160°F	71°C
Inlet Ports (2)	1/2" NPTF	1/2" NPTF
Discharge Ports (3)	3/8" FPM*	3/8" FPM*
Weight	60 lbs	27.3 kg
Dimensions	19.53 x 12.99 x 6.44	496 x 330 x 163.5 mm

*Autoclave engineering medium pressure



www.catpumps.com • email: techsupport@catpumps.com

1681 - 94th Lane NE, Minneapolis, MN 55449-4324 • Phone: 763-780-5440 • Fax: 763-780-2958



The Pumps with Nine Lives