

# Kerosene Indirect Ductable

## Job Site Series

Mi-T-M introduces the Job Site Series of indirect heaters. Designed for use in ventilated buildings and construction sites for drying and heating large areas.



MH-0300-0MIH

**All Models Feature**

**Frame**

- Powder coated steel frame, handle and tank
- Heavy-duty tires for easy mobility

**Burner**

- Stainless-steel combustion chamber
- Direct spark ignition

**Motor**

- Heavy-duty, high quality cast aluminum electric motor

**Components**

- Safety switch prevents overheating
- Thermostatically controlled
- Suitable for air ducting
- Easy to operate controls
- High capacity fuel tank
- Electronic flame control
- Automatic ignition
- Water resistant control box
- Automatic fuel shut-off

**Warranty on All Models**



**MH-0092 Additional Features**

**Components**

- Rotary pump compressor
- Compact design
- Thermostat plug

**MH-0125 & MH-0300 Additional Features**

**Frame**

- Front foot brace
- Rugged steel body

**Components**

- High thermal efficiency
- Control panel with thermostat plug, reset push button and safety air pressure switch
- Heated fuel filter for more reliable starts in subzero temperatures
- High pressure fuel pump
- Vacuum sensor helps prevent heater lock out

**For use in construction sites and applications where the heat will be ducted into a building.**

Model Number	MH-0092-0MIH	MH-0125-0MIH	MH-0300-0MIH
Heat Output	92,000 BTU	125,000 BTU	300,000 BTU
Hot Air Flow	557 CFM	1,180 CFM	2,650 CFM
AC Power	115V, 60Hz, 1Ø, 4.0 Amps	115V, 60Hz, 1Ø, 7.0 Amps	115V, 60Hz, 1Ø, 12.5 Amps
Power Consumption	250 watts	460 watts	800 watts
Fan Static Pressure	0.5-inch WC	0.7-inch WC	0.8-inch WC
Fuel Tank Capacity	12.2-gallons	13.5-gallons	36.0-gallons
Fuel Consumption	0.66 gal./hr.	0.9 gal./hr.	2.1 gal./hr.
Temperature Rise	120°F	130°F	130°F
Max. Output Temperature	240°F	240°F	240°F
Max. Operating Hours	18 hours	15 hours	17 hours
Duct Size (LxDiameter)	15-feet x 12-inch	25-feet x 12-inch	25-feet x 18-inch
Dimensions (LxWxH)	36.6in.x22.1in.x24.6in.	54.8in.x27.6in.x32.7in.	68in.x29.5in.x40.4in.
Ship Wt.	93 lbs.	162 lbs.	290 lbs.
Net Wt.	88 lbs.	154 lbs.	282 lbs.



**Important Notes**

- Not for use in residential living areas or inadequately ventilated areas
- Proper ventilation required during operation
- Must be plugged into an approved standard electrical outlet for operation

**Functions on: Kerosene or No. 1 and No. 2 fuel oil**

Specifications subject to change without notice. Use in accordance with any and all state or local codes, regulations and/or ordinances. Please see heater "Owner's Manual" included with each heater for a complete list of important safety information. These specifications are estimates only.

**ACCESSORIES**

Part Number	Description	Fits Models
68-4001	Thermostat control with 20-foot cord - For light party use	All models
68-4002	Thermostat control with 20-foot cord - For use on a construction site	All models
68-4003	Duct adapter - Connects ducting to heater	MH-0092-0MIH
68-4004	Duct adapter - Connects ducting to heater	MH-0125-0MIH
68-4005	Duct adapter - Connects ducting to heater	MH-0300-0MIH
68-4006	15-foot x 12-inch black flexible air ducting - Ducting directs heat	MH-0092-0MIH
68-4007	25-foot x 12-inch black flexible air ducting - Ducting directs heat	MH-0125-0MIH
68-4008	25-foot x 18-inch black flexible air ducting - Ducting directs heat	MH-0300-0MIH
68-4056	Flue extension - Elevates rain cap	All models
68-4067	Rain cap - Protects flue from moisture when unit is left outside	All models