



### SPECIFICATIONS

Part Number	YCV14FSS	YCV38FSS	YCV12FSS
Flow Rate	6.5 GPM	10.5 GPM	21.0 GPM
Max. Pressure	5800 PSI	5800 PSI	5800 PSI
Max. Temperature	195° F	195° F	195° F
Cracking Pressure	3 PSI	5 PSI	8 PSI
Port Size	1/4-19 BSPP-FxF	3/8 BSPP-FxF	1/2 BSPP-FxF
Dimensions	17mm hex x 1.85"	22mm hex x 2.13"	27mm hex x 2.60"
Weight	.12 lb.	.23 lb.	.42 lb.
Material	Stainless Steel, Viton		

### PARTS LIST

YCV14FSS: Y60.2030.00  
 YCV38FSS: Y60.2020.00  
 YCV12FSS: Y60.2070.00

No.	Part Number	Description	Qty.
1.	Y10.3049.00	O-Ring, .208" ID x .070" CS, YCV14FSS	1
	Y10.3055.10	O-Ring, .301" ID x .070" CS, YCV38FSS	
	Y10.3175.10	O-Ring, .424" ID x .103" CS, YCV12FSS	
2.	Y60.2034.51	Valve, SS, YCV14FSS	1
	Y60.2023.51	Valve, SS, YCV38FSS	
	Y60.2062.51	Valve, SS, YCV12FSS	
3.	Y60.2031.51	Body, SS, 1/4 BSPP-FxF	1
	Y60.2024.51	Body, SS, 3/8 BSPP-FxF	
	Y60.2061.51	Body, SS, 1/2 BSPP-FxF	
4.	Y60.2033.51	Disc, SS, YCV14FSS	1
	Y60.2021.51	Disc, SS, YCV38FSS	
	Y60.2063.51	Disc, SS, YCV12FSS	
5.	Y60.2032.51	Spring, SS, YCV14FSS	1
	Y60.2022.51	Spring, SS, YCV38FSS	
	Y60.2064.51	Spring, SS, YCV12FSS	
6.	Y16.1825.00	Screw, M3 x 6, YCV14FSS	1
	Y16.1830.00	Screw, M4 x 8, YCV38FSS	
	Y16.1832.00	Screw, M6 x 8, YCV12FSS	

