LANDA®


Industrial Pressure Washers ...Built Right to Do the Job Right

Since 1969

SLX-SLT

The Only Portable Hot Water Pressure Washer that Delivers 200°F Cleaning at up to 10 GPM

- Dual-Gun Ready
- Powered by Gasoline or Diesel: Diesel-Heated
- Belt-Drive Landa Pump with 7-Year Warranty
- 3/4" Schedule 80 Coil



■ Extra-large **Heating Coil** made of cold-rolled, 3/4" Schedule 80 steel pipe with 5-year warranty; features Stainless Steel Top Wrap: unique lift-out design for easy and quick Coil Access.

■ Rugged 2" x 4" x 1/8" thick box steel frame, with compact footprint, shields key components; further protected by weather-resistant Epoxy Powder Coat finish: Power Platform is vibration isolated to minimize frame stress.

> ■ Water-resistant, metal Control Panel has adjustable thermostat, combination hour meter and tachometer, volt meter, burner switch and tri-lingual operating instructions for added safety.

> > Adjustable Detergent and Steam Valves provide precise metering of soap and on-demand wet-steam cleaning.

■ Gasoline-powered Vanguard and Honda Engines, or watercooled, 16-27 hp diesel Kohler Engine all come with keyed electric starter for easy start-up and protection against unauthorized use; polyurethane Battery Box with vibration isolators protects and firmly secures battery (battery not included).

■ Efficient 2,000-Watt Generator produces reliable power for burner.



■ 50 ft. of double-wire braid

settled debris.

low RPM for long life, 7-year warranty, with

single-rail true-track

Pulley Adjustment.

Illustrated

protection.

Warning Labels universally under-

standable for liability

■ 30-gallon diesel

and 16-gallon gasoline

Fuel Tanks (15-gallon

diesel and 10-gallon

gasoline on SLT) pro-

vide hours of uninter-

rupted operation; with

elevated fuel lines to

avoid suctioning of

High Pressure Hose rated for up to 6000 PSI and featuring a 24-inch safety hose guard for operator burst protection.

■ High-efficiency **Burner**, with dual rings for "dialing in" air flow, has a Fuel-Water Separator for fuel pump protection.



■ Many Safety Features, including a rupture disk, thermal pump protector, flow switch, unloader valve, and safety lock on the trigger gun.

Corrosion-resistant Float Tank has stainless steel inlet filter and 3/4" float valve with anti-siphon backflow protection; also allows for introduction of detergents in highpressure mode.

SLX

■ Insulated, fatigue-free Trigger Gun, with swivel crimp fitting for a tangle-free hose. Stainless steel, dual-lance Variable Pressure Wand features an ergonomic design and easy adjusting of the water pressure while cleaning.

www.landa.com

LANDA®

Industrial Pressure Washers ...Built Right to Do the Job Right

Since 1969

SLX-SLT

The Only Portable Hot Water Pressure Washer that Delivers 200°F Cleaning at up to 10 GPM

- Dual-Gun Ready
- Powered by Gasoline or Diesel; Diesel-Heated
- Belt-Drive Landa Pump with 7-Year Warranty
- 3/4" Schedule 80 Coil

WHY CHOOSE LANDA'S SLX or SLT

When it comes to heavy-duty grease or grime, most high-volume, hot water pressure washers fall short with their 150°F water. Landa's SLX, and smaller SLT, are the first power washers ever designed to deliver a high-volume flow at 200°F water, hot enough to melt the toughest of oily messes. The SLX delivers enough hot water flow—up to 9.5 GPM—that you can operate two spray guns at the same time! Other benefits include:

QUALITY: Packed with Landa quality throughout, the SLX and SLT feature a top-of-the-line, belt-drive Landa Pump with 7-year warranty and low RPM for extended life, as well as a giant Schedule 80 heating coil, made of up to 300 ft. of 3/4-inch steel pipe with 5-year warranty.

DURABILITY: Extraordinarily rugged frame is made of 2-by-4-inch box steel with an all-metal power platform cushioned by 10 vibration isolators to minimize frame stress.

EFFICIENT: The SLX-SLT is heated by a high-efficiency Beckett burner with dual rings for dial-in air flow. The 3/4" heating coil is amazingly efficient due to its unique "breathing" design so it heats quieter while promoting optimum heat exchange.



FUNCTIONAL: The SLX-SLT has a remarkably compact footprint, is certified to UL-1776 safety standards, is pre-plumbed for drawing water from an auxiliary tank, has six forklift guides for portability and the control panel is ideally positioned for curb access when the unit is mounted on a trailer or truck bed.

SLX and SLT Specifications											
Model No.	GPM	PSI	Engine	CCs(HP)	Engine Fuel	Gas Tank	Diesel Tank	Pump RPM	BTU's	LxWxH	SHIP WT
SLX10-25324E	9.5	2500	Honda	670(24)	Gasoline	16	30	1560	887,000	65" x 36" x 58"	2020 lbs.
SLX10-25824E	9.5	2500	Kohler	1028(27)	Diesel	N/A	40	1470	887,000	65" x 36" x 58"	2160 lbs.
SLT5-30224E	5.2	3000	Vanguard	479(16)	Gasoline	10	15	1295	485,000	55" x 32" x 51"	1210 lbs.
SLT6-32324E	5.9	3200	Honda	614(20)	Gasoline	10	15	1570	550,000	55" x 32" x 51"	1220 lbs.
SLT8-30324E	7.8	3000	Honda	670(24)	Gasoline	10	15	1470	728,000	55" x 32" x 51"	1230 lbs.
SLT5-30824E	4.4	3000	Kohler	686(16)	Diesel	N/A	26	1295	410,000	62" x 32" x 53.5"	1715 lbs.
SLT6-32824E	5.9	3200	Kohler	1028(27)	Diesel	N/A	26	1470	588,000	62" x 32" x 53.5"	1785 lbs
SLT8-30824E E=Electric Start	7.8	3000	Kohler	1028(27)	Diesel	N/A	26	1560	728,000	62" x 32" x 53.5"	1850 lbs.

Note: Landa is constantly improving undergoing in expertised. Experimentally improving undergoing in quantity improving undergoing in quantity in quan



Distributed by:



Power Wash Detergents:

Landa has an extensive line of detergents formulated specifically for use with hot water pressure washers such as the SLX and SLT

www.landa.com