

# EQUIPMENT TRADE SERVICE CO INC. CLEANING PRODUCTS SPECIALISTS

20 E. Winona Ave. Norwood, PA 19074 Ph. (610) 583-7657 Fax. (610) 583-5479 www.etscompany.com

REAR VIEW

# **POWER WASH HOSE REELS**

Rapid Reel Industrial hose reels by Reel Quick, Inc. Since 1991, we've made reels which are unsurpassed in quality of design, durability and ease of operation. Rapid Reel Industrial Hose Reels are designed specifically for heavy and extreme-duty applications. Built to industrial-strength standards, Rapid Reel Hose Reels provide years of leak-free operation and exceptional performance even under demanding conditions.

### **4000 SERIES**

Built to industrial-strength standards, Rapid Reel Industrial Bolt-On Reels provide years of leak-free operation and exceptional performance under rigorous industrial conditions. Plus, with dozens of MOUNTING OPTIONS, this is the most versatile reel series on the market!



#### **Great For:**

- Wall Mountings
- Vehicle & Trailer Mountings
- Portable Reels (Carts & Caddies)
- Washer Frame Mountings

#### MOUNTING OPTIONS:



	Model	Size	Flow	Cap.	Ship Wt.	Max. Pressure	Max. Temp	Warranty
	4413-PW1	Medium	3/8"	100 ft.	18 lbs.	5000 PSI	325°F	2 Years
	4416-PW1	Large	3/8"	200 ft.	22 lbs.	5000 PSI	325°F	2 Years
×	4916-PW1	X-Large	3/8"	300 ft.	25 lbs.	5000 PSI	325°F	2 Years
	4413-PW2	Medium	1/2"	75 ft.	18 lbs.	5000 PSI	325°F	2 Years
	4416-PW2	Large	1/2"	150 ft.	22 lbs	5000 PSI	325°F	2 Years
X	4916-PW2	X-Large	1/2"	200 ft.	25 lbs	5000 PSI	325°F	2 Years

## **5500 SERIES**

The workhorse of the Rapid Reel pivoting line, the 5500 Series reels offer all the Rapid Reel Industrial features, on a revolutionary pivoting arm. A huge selection of brackets provides unmatched mounting versatility.



#### **Great For:**

- Wall Mountings
- Portable Reels (Carts & Caddies)
- Washer Frame Mountings

#### **MOUNTING OPTIONS:**

Pivot Lock



Model	Size	Flow	Cap.	Ship Wt.	Max. Pressure	Max. Temp	Warranty
5513-PW1	Medium	3/8"	100 ft.	35 lbs.	5000 PSI	325°F	2 Years
5516-PW1	Large	3/8"	200 ft.	37 lbs.	5000 PSI	325°F	2 Years
5513-PW2	Medium	1/2"	75 ft.	35 lbs.	5000 PSI	325°F	2 Years
5516-PW2	Large	1/2"	150 ft.	37 lbs	5000 PSI	325°F	2 Years