


EZ Series 44 S

2500 / 3000 PSI, Triplex Plunger Pump

FEATURES


- Solid ceramic plunger design
- Flex coupling and bell housing available for direct drive
- Forged brass manifold with an exclusive lifetime warranty and 4:1 hydrostatic rating
- Die-cast, anodized aluminum, oil-bath crankcase
- Premium roller bearing
- Unitized stainless steel inlet and discharge valves
- Available in “L” left-handed versions




SPECIFICATIONS

Pump Model	EZ2536S	EZ2542S	EZ2545S	EZ2555S	EZ3040S	EZ3042S
Maximum Volume	3.6 GPM	4.2 GPM	4.6 GPM	5.5 GPM	4.0 GPM	4.2 GPM
Maximum Discharge Pressure	2500 PSI				3000 PSI	
Maximum Pump Speed	1750 RPM		3400 RPM			1750 RPM
Maximum Inlet Pressure	125 PSI					
Maximum Inlet Vacuum	3 ft. water (2.6 in. Hg)				9 ft. water (7.9 in. Hg)	
Bore	.708 in. / 18 mm		.591 in. / 15 mm			.708 in./18 mm
Stroke (in./mm)	.433 / 11	.512 / 13	.433 / 11	.512 / 13	.374 / 9.5	.512 / 13
Crankcase Oil Capacity	14.0 oz.					
Maximum Fluid Temperature	165°F					
Inlet Port Thread	1/2-14 BSPP-F					
Discharge Port Thread	3/8-19 BSPP-F					
Shaft Diameter.	.945 in. / 24 mm					
Weight	18 lbs.					
Dimensions	8.6 x 8.7 x 5.5 in.					

DIMENSIONAL DRAWING



EZ Series 44 S – 2500/3000 PSI **GENERAL PUMP** A member of the Interpump Group



PARTS LIST

Item	Part No.	Description	Kit No.	Qty.	Item	Part No.	Description	Kit No.	Qty.	Item	Part No.	Description	Kit No.	Qty.
1.	44120441	Manifold		1	21.	90489200	Key		1	42.	44216170	Intermediate Ring	128, 131	3
	(18mm: EZ2536S, EZ2542S, EZ3042S)				22.	44050066	Plunger Guide		3		(18mm: EZ2536S, EZ2542S, EZ3042S)			
	44120041	Manifold		1	23.	44030022	Connecting Rod		3		52216670	Intermediate Ring	89, 130	
	(15mm: EZ2545S, EZ2555S, EZ3040S)				24.	90392000	O-Ring		1		(15mm: EZ2545S, EZ2555S, EZ3040S)			
2.	99317500	Screw		8	25.	44160022	Rear Cover		1	43.	90268300	Packing	127, 131	3
3.	96701400	Washer		8	26.	99183700	Screw		5		(18mm: EZ2536S, EZ2542S, EZ3042S)			
4.	90384100	O-Ring	123	6	27.	90358500	O-Ring		1		90262200	Packing	88, 130	
5.	36200366	Valve Seat	123	6	28.	98204100	Cap Screw		1		(15mm: EZ2545S, EZ2555S, EZ3040S)			
6.	36200176	Valve	123	6	29.	97734000	Pin		3	44.	90268200	Packing	127, 131	3
7.	94737600	Spring	123	6	30.	96735000	Washer		3		(18mm: EZ2536S, EZ2542S, EZ3042S)			
8.	36202551	Valve Cage	123	6	31.	90502200	Anti-Extrusion Ring		3		90262000	Packing	88, 130	
9.	90384700	O-Ring	124	6	32.	90357200	O-Ring		3		(15mm: EZ2545S, EZ2555S, EZ3040S)			
10.	98222600	Cap Screw	124	6	33.	44040109	Plunger, 18mm		3	45.	44100151	Head Ring	129, 131	3
11.	36711501	Valve Assembly	123	6		52040009	Plunger, 15mm	(EZ2536S, EZ2542S, EZ3042S)			(18mm: EZ2536S, EZ2542S, EZ3042S)			
12.	99180700	Screw		4				(EZ2545S, EZ2555S, EZ3040S)			51100051	Head Ring	90, 130	
13.	50150074	Bearing Cover		1	34.	96700800	Washer		3		(15mm: EZ2545S, EZ2555S, EZ3040S)			
14.	44211801	Spacer		1	35.	92221600	Nut		3	46.	98210000	Cap Screw		1
15.	90409700	O-Ring		1	36.	90164100	Oil Seal		1	47.	98217600	Cap Screw		1
16.	91832800	Ball Bearing		1	40.	90361200	O-Ring	126, 131	3	48.	96738000	Washer		1
	91304200	Ball Bearing (EZ3040S, EZ3042S)				(18mm: EZ2536S, EZ2542S, EZ3042S)				49.	96751400	Washer		1
17.	90161400	Oil Seal	23	3		90361200	O-Ring	125, 130		50.	98196600	Cap Screw		1
18.	44010022	Crankcase		1		(15mm: EZ2545S, EZ2555S, EZ3040S)				51.	90268400	Seal, Low Press.	127, 131	3
19.	98210300	Oil Dip Stick		1	41.	44080170	Packing Retainer	126, 131	3		(18mm: EZ2536S, EZ2542S, EZ3042S)			
20.	44020035	Crankshaft (EZ3040S)		1		(18mm: EZ2536S, EZ2542S, EZ3042S)					90261700	Seal, Low Press.	88, 130	
	44020335	Crankshaft (EZ2535S, EZ2545S)				44080070	Packing Retainer	125, 130			(15mm: EZ2545S, EZ2555S, EZ3040S)			
	44020635	Crankshaft (EZ2542S, EZ2555S, EZ3042S)												

REPAIR KITS

KIT NO.	All	(15mm) (18mm)	(15mm) (18mm)	(15mm) (18mm)	All	All	(15mm) (18mm)	(15mm) (18mm)
	23	88 or 127	89 or 128	90 or 129	123	124	125 or 126	130 or 131
ITEM NO.s INCLUDED IN KIT	17	43, 44, 51	42	45	4, 5, 6, 7, 8, (11)	9, 10	40, 41	40, 41, 42, 43, 44, 45, 51
NUMBER OF ASSEMBLIES IN KIT	3	3/6	3	6	6	6	3	1
NUMBER OF CYLINDERS KIT WILL SERVICE	3	3	3	3	3	3	3	1

TORQUE SPECS*

Position	Ft.-lbs.	N-M
2	14.7	20
10	73.7	100
12	7.3	10
26	7.3	10
28	14.7	20
35	11.0	15
39	14.7	20
46	29.4	40
47	29.4	40
50	9.6	13

*Decrease torque by 20% if threads are lubricated.